

BM-Slim2

Ultra-slim FAP20 Authentication Scanner Module



BM-Slim2 is FAP20 certified fingerprint scanner featuring an array of cutting-edge technologies. Along with its 13.5mm slim optical sensor, BM-Slim2 features Xperix's proprietary Multi-dynamic Range(MDR) technology, FBI PIV/Mobile ID FAP20 compliance and Android device support. BM-Slim2 also provides developers more physical flexibility with its reduced form factor and the ultra-slim optical sensor ensures robust operation over time. BM-Slim2 provides advanced artificial Intelligence-based Live Finger Detection technology which is compliant with ISO 30107-3 PAD Level 1 & 2 Standard. Applying LFD technology, BM-Slim2 distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film, and more.



BM-Slim2

Ultra-slim FAP20 Authentication Scanner Module

FEATURES



- World's thinnest 13.5 mm FAP20 certified optical fingerprint scanner



- FBI PIV and FBI Mobile ID FAP20 certificates
- Image compression standard: WSQ



- Capturing high-quality fingerprint images even when the finger is dry & wet.
- Operates under direct sunlight up to 100,000 LUX



- Live Fingerprint Detection (LFD) Technology
 - ISO 30107-3 Compliant (PAD Level 1 & 2)
 - Distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film and more



- Easy Integration
 - BioMini SDK for easy application development
 - Android, MS Windows & Linux compatible
 - Multi-threaded code design for multi-core CPU utilization



- No need to type in a password
- Instant login by touching your finger

SPECIFICATIONS

	Image Quality Standards	FBI PIV / FBI Mobile ID FAP20
	Live Finger Detection	O
Sensor	Sensor Type	Optical
	Resolution	500 ppi
	Gray Scale	256 level
	Platen Size (W x L mm)	16.5 x 21.0
	Sensing Area (W x H mm)	15.24 x 20.32
	Image Size (W x H pixels)	300 x 400
H/W	Interface	USB 2.0 High Speed
	Operating Temperature(°C)	-10 - 50°C
	Operating humidity	0 - 90% RH
	Dimensions (W x L x H mm)	59 x 32 x 13.5 mm
S/W	Windows	Windows XP, Vista, 7, 8, 8.1, 10 32/64bit
	Linux	Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64bit
	Android Android 5.0 or later	O
	Image Format	RAW, BMP, WSQ, ISO 19794-4
	Template Type	Xperix, ISO19794-2, ANSI-378
Certification	CE	O
	FCC	O
	KC	O
	UL / CB	O
	IEC62471	O
	WEEE	O
	WHQL	O



Xperix Inc.

#305-308, 3F, Building A, Tera Tower 2, 201 Songpa-daero, Songpa-gu, Seoul, Republic of Korea
 T +82 1588 8817 E sales_id@xperix.com www.xperix.com

©2024 Xperix Inc. Xperix and identifying product names and numbers herein are registered trade marks of Xperix Inc. All non-Xperix brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.